

MESA CAP UNIT

MAX. DEFLECTION, 16"

PAVEMENT/OBSTRUCTION SECTION DEPTH VARIES, REFER TO CONTRACT DRAWINGS.

5 11

4" (MIN.)

MESA STANDARD UNIT

TENSAR STRUCTURAL GEOGRID

HORIZONTAL PAVEMENT STRUCTURE

MESA CAP UNIT

SUPERELEVATED SECTION

PAVING SECTION/OBSTRUCTION

MESA STANDARD UNIT

4" (MIN.)

TENSAR STRUCTURAL GEOGRID

SUPERELEVATED PAVEMENT/OBSTRUCTION STRUCTURE

NOTE:

CONTRACTOR IS RESPONSIBLE TO COORDINATE THE PLACEMENT OF THE GEOGRID TO AVOID CONFLICT WITH THE CONTRACT PAVEMENT/OBSTRUCTION SECTION. GEOGRID MUST BE SEPARATED FROM THE PAVEMENT/OBSTRUCTION SECTION BY A MINIMUM OF 4".

GEOGRID PLACEMENT AT PAVEMENT/OBSTRUCTION SECTION


NOT TO SCALE

DESCRIPTION:

GEOGRID PLACEMENT AT PAVEMENT/OBSTRUCTION SECTION

FILE NAME:

ME-ST-OB-001.DWG



MESA[®]

RETAINING WALL SYSTEMS